



WELCOMES YOU TO THE *SAPLING FIREBOX*

We hope you get many years of enjoyment from your *Sapling Firebox*. Here's how to start!

Getting Ready to Assemble your *Sapling Firebox*

What you will need besides your *Sapling*:

1. vegetable or olive oil;
2. an electric drill with a 3/32" bit;
3. a Phillips screwdriver.

Assembling your *Sapling Firebox*

1. Your *Sapling* has arrived in multiple boxes. Remove all parts from inside the boxes. Inside the boxes, you will have:
 - one (1) *Sapling* barrel;
 - one (1) *Sapling Stack Flange*;
 - one (1) *Sapling Stack Elbow*;
 - one (1) *Sapling Stack Bracket*;

- two (2) pieces of *Sapling Stove Pipe*;
- a smaller box containing:
 - one (1) door;
 - one (1) door frame;
 - two (2) leg sets;
 - seven (7) self-drilling screws;
 - two (2) clevis pins;
 - eight (8) each bolts, nuts and lock washers for the legs; and
 - sixteen (16) each bolts, nuts and lock washers for the door frame.

2. First, assemble the leg sets onto the barrel using the predrilled holes and the nuts, bolts and lock washers.

HINT: The easiest way to assemble the legs is as follows. If you have already installed the door, uninstall it. Orient your Sapling “bottom-up,” with the cavity facing down. (It helps to have a skinny table or workbench or pair of sawhorses to do this while steadying the unit.) Align the holes in each leg set (so that the feet face the rear of the machine) on the corresponding holes on the barrel and push a bolt through each pair of holes. When all bolts have been inserted, reorient the unit exit-hole down (door-side up) with the cavity facing you. Install the lock washers and nuts and tighten!

3. Assemble the door frame onto the barrel by using the nut and bolt assemblies provided, making sure that the catch for the door latch is on the left and the hinge pieces on the right.
4. Next, assemble the door to the frame by carefully aligning the holes on the door hinge piece just above the holes on the frame hinge piece. Then, gently tap the clevis pins in place to secure the door to the frame.
5. Center the *Sapling Stack Flange* to the exit hole in the back of the unit. Mark the location of the four predrilled holes in the takeoff on the back of the barrel with pencil, chalk or a nail. Predrill those holes. Using four of the screws provided, affix the takeoff to the back of the barrel. (The screws are self-tapping, and, when enough pressure is applied, will eventually tap into the barrel without the need for drilling holes. However, we recommend predrilling the holes for a smoother assembly.)
6. Slide the *Sapling Stack Elbow* on the flange affixed to the back of the barrel. Adjust the elbow so that the exit of the elbow is pointed straight up and the elbow is inserted into the flange as far as possible. Screw the elbow to the flange by driving one self-tapping screw straight down through the place where the elbow and flange overlap. Use the remaining self-tapping screw to further stabilize the elbow, as needed.
7. Fit a piece of *Sapling Stove Pipe* onto the elbow exit.
8. Fit the second piece of pipe onto the first piece of pipe.
9. Place a layer of sand and/or ashes in the bottom of your barrel. Two inches or so will do. **CAUTION:**

failure to place an insulating layer in the bottom of your barrel can result in catastrophic failure – the fire may burn right through your barrel! If you are insulating your barrel with *Sapling Firebrick* or the like, you may choose to skip this step or go belt & suspenders. Up to you!

10. Coat the exterior of the barrel with a thin layer of vegetable or olive oil (apply with a paper-towel or rag). Done!

Maintaining your *Sapling Firebox*

The best practice is to clean out the ash and oil the inside of your barrel with vegetable or olive oil when not in use for extended periods of time, and, unless your *Sapling* can be stored in a garage or barn, you should cover it when not in use. Consider purchasing the *Sapling Grill Cover* for this purpose. If water gets in your barrel, be sure to dump it out, dry it out, and apply another layer of oil to discourage rust.

Expansion and contraction caused by heating, cooling and exposure to the elements may eventually cause some cracking, thinning and/or flaking in the paint on your *Sapling*. If you notice this, after the barrel has cooled, sand the area with 100 grit sandpaper and repaint with *Sapling Flat Black Paint*, or the equivalent.

Consider purchasing the *Sapling Care Kit*, which includes everything you need for maintaining the *Sapling* and all its accessories.